



Range of axial flow fans designed to exhaust air directly to the outside.

All the fans are manufactured from injection moulded plastic and fitted with automatic shutter and single phase 230V-50Hz, class B motor, thermal protection, "fuse". All the fans are class II insulation and IPX4 rated.





External shutter
 Overpressure shutter.



Safety guards
 Guards fitted at the inlet and outlet of the fan to prevent the entry of any foreign objects.


EASY INSTALLATION IN GLASS OR WALL



Mounting in glass:
 Maximum diameter (3 to 6 mm).
 Cut hole diameter (mm).
 HCM-150 N: 183 to 188
 HCM-180 N: 220 to 225
 HCM-225 N: 262 to 267

Mounting in wall:
 Cut hole diameter (mm).
 HCM-150 N: 183 to 188
 HCM-180 N: 220 to 225
 HCM-225 N: 262 to 267

DIMENSIONS (mm)



Model	ØA	ØB	C	D	E	F
HCM-150 N	214	174	60	88	35	98
HCM-180 N	255	205	86	120	35	135
HCM-225 N	298	248	89	119	35	125

ACCESSORIES



REB
 Electronic, single phase speed controller.

TECHNICAL CHARACTERISTICS

Model	Speed (rpm)	Maximum absorbed power (W)	Voltage (V) 50 Hz	Maximum airflow (m³/h)	Sound pressure level* (dB(A))	Weight (kg)	Electric scheme*
HCM-150 N	1900	25	230	400	40	0,9	11
HCM-180 N	2000	28	230	600	41	1,7	11
HCM-225 N	1700	40	230	900	45	1,8	11

* Sound pressure level measured at 1,5 m, at the inlet side, in free field.
 ** See section Electric Schemes.